

Clone a production helpdesk to a secondary test instance

Deskpro Legacy - تعليقات (0) - Christopher Nadeau - 2017-11-09

We recommend you configure a test instance of your helpdesk to test any major updates before trying to put them live

:This is easy to accomplish by following the "[Moving Servers](#)" guide

:With the following notes

Disable cron on the test instance before importing your database (1)

To ensure email does not get processed into your test instance, you need to disable the .cron job on the test server BEFORE you import your database on the test instance

You can choose to enable cron again *after* you have logged-in to the test instance as an admin to disable/delete the active email accounts that exist on your live helpdesk. The point here is that you do NOT want email processing from live email accounts into your test instance. So you need to delete them (and possibly replace them with test accounts) if you .want to enable cron on the test instance

Edit config/advanced/config.settings.php (2)

:Add the following lines

```
SETTINGS['core.filestorage_method'] = 'db';$  
$SETTINGS['core.filestorage_s3_key'] = 'x';  
$SETTINGS['core.filestorage_s3_secret'] = 'x';  
;$SETTINGS['core.filestorage_s3_bucket'] = 'x'
```

This will force the system to store files in the database. This is a safety precaution to ensure if you are using some other mechanism like S3, that deleting a file in this test instance does .not delete the file in S3 which would still be in use by your live helpdesk

You may also wish to enable the `disable_outgoing_email` option in this file to disable all
outgoing email (e.g. this will ensure end-users don't get test emails etc