



[Using Deskpro](#) > [Reports](#) > [Reporting on Reopened Tickets](#) < [قاعدة المعلومات](#)

Reporting on Reopened Tickets

[Reports](#) - [تعليقات \(.\)](#) - Matthew Wray - 2023-08-24

You can use the [tickets_logs table](#) to report on tickets that have been reopened after an Agent or User has changed the status to Resolved.

Example Query

The query below will generate a list of reopened ticket IDs with the subject, agent name, and user name

```
SELECT tickets_logs.ticket.subject, tickets_logs.ticket.agent, tickets_logs.ticket.person.name
FROM tickets_logs
WHERE tickets_logs.action_type = 'changed_status' AND tickets_logs.id_before = '200' AND tickets_logs.id_after
'<>'210
GROUP BY tickets_logs.ticket.id
```

In this example, the id 200 represents Resolved. Hence, the status change being measured is from 'Resolved' to another status.

Handling Archiving in the query

You can see we've also used the ID 210 in the query. This represents the Archived status

Archiving is an optional feature, but if it's enabled you would need to ensure you have tickets moved from Resolved -> Archived excluded from the stat as this would not constitute a reopen

Hence, we use the tickets.id_after function alongside the does not equal operator <> to exclude them **tickets_logs.id_after <> '210**