Using an opcode cache (OPCache, APC or WinCache)

Christopher Nadeau - 2023-10-26 - Коментари (2) - Deskpro Legacy

Deskpro is a large PHP application with hundreds of thousands of lines of PHP code in hundreds of source files. To drastically improve performance, we highly recommend using an opcode cache (also known as a bytecode cache) such as APC or WinCache. An opcode cache stores precompiled versions of scripts in memory, removing the need for PHP to load and parse scripts on every request.

OPCache (PHP 5.5 or above)

PHP 5.5 or higher comes with a bundled opcode cache (OPCache). If possible, we recommend you use PHP 5.5 - this removes the need to install the opcode cache separately.

If you have PHP 5.5, DO NOT install WinCache or APC as they are not required.

If you have 5.5 or above but the installation wizard prompts you to install OPCache, you may need to add these lines to your *php.ini* to enable it:

```
opcache.enable=1
```

and

```
zend_extension=/full/path/to/opcache.so
```

or on Windows:

```
zend_extension=php_opcache.dll
```

In some cases you may need to specify the full path to php_opcache.dll, e.g.:

```
C:\Program Files (x86)\PHP\v5.5\ext\php_opcache.dll
```

There are other OPCache settings in php.ini used to tune performance. We suggest starting with the following settings for most systems:

```
opcache.memory_consumption=128
```

If you have a server with lots of RAM (8 GB or more), try increasing *opcache.memory_consumption* to 256.

```
opcache.interned_strings_buffer=8opcache.max_accelerated_files=4000opcache.revalidate_freq=60opcache.fast_shutdown=1opcache.enable_cli=0
```

See http://php.net/manual/en/opcache.installation.php for more information on OPCache settings.

Restart your webserver after editing *php.ini* to apply changes.

ONLY if you can't upgrade your PHP version to 5.5, install a separate opcode cache from the ones below.

WinCache on Windows

If you are using IIS on Windows you can install WinCache from Microsoft's IIS website at http://www.iis.net/downloads/microsoft/wincache-extension

Installing APC on Linux with PECL

You can compile and install APC manually via PECL.

```
pecl install apc
```

For more information refer to the PHP manual and the APC PECL page:

- http://pecl.php.net/package/apc
- http://php.net/manual/en/install.pecl.pear.php

Installing APC on Debian or Ubuntu

```
sudo apt-get install php5-dev
sudo pecl install apc
sudo /etc/init.d/apache2 restart
```

Installing APC using yum on RedHat or CentOS

If you have installed PHP using yum, you can activate APC using yum as well:

```
yum install php-pear php-devel
pecl install apc
service httpd restart
```