

DPQL v2

2018-05-21 - Benedict Sycamore - Коментари (0) - Product

As part of product release Deskpro 2018.1, we've introduced a whole new reporting system. You can learn more about all that [here](#).

This also means you can expect some changes and improvements to the way DPQL works in reports, and this article has been written to simply explain each of those changes.

All DPQL functions start with DPQL_ prefix

To make it easy to determine which functions are DPQL-specific and which are part of standard MySQL functions, DPQL functions now have to include the prefix 'DPQL_' -e.g. DPQL_COUNT

This now means that functions without the prefix operate just as they would when using standard MySQL.

Support for subqueries

You can now nest a query inside a larger query. For example:

```
SELECT tickets.id
FROM tickets
WHERE tickets.id IN (
  SELECT tickets.id
  FROM tickets
  WHERE tickets.ref LIKE 'AAAA-%'
)
```

Support for unions

You can now combine the results of two queries into a single query. For example:

```
SELECT tickets.id FROM (  
  
  (SELECT tickets.id FROM tickets)  
  
  UNION  
  
  (SELECT tickets.id FROM tickets)  
  
) as t1
```

No more DISPLAY line

Previously, in DPQL1, a query would start with 'DISPLAY TABLE' or the type of report you had selected to display. This is no longer a feature. Admins now simply choose the type of graph as an option rather than it being coded into the query itself.

New function 'DPQL_JSON_EXTRACT'

This function operates in a similar way to MySQL's [JSON_EXTRACT](#). It lets you SELECT a field in the database that is stored as JSON, and extract a specific value for display.

This function only works in the SELECT clause (i.e. a value you want to display) because the decoding only happens in PHP. It can be used to support displaying specific data from a JSON blob.

New function 'DPQL_HIERARCHY'

Deskpro has a number of fields that have hierarchies such as Departments, Organizations, Categories, Products and Custom choice fields. You can use DPQL_HIERARCHY to denote hierarchy in reports. This allows you to see a total count for one field and all sub-fields. The below image demonstrates a few real life examples of what the reporting will allow.

- DPQL_HIERARCHY can only be used in a GROUP BY.
- DPQL_HIERARCHY can only be used in the *first* group by. A current limitation. You can't use it as a secondary group by param.

The signature for DPQL_HIERARCHY is:

- DPQL_HIERARCHY(*field*, *minDepth*, *maxDepth*)
- The field can be any field in deskpro where hierarchy exists (custom fields, departments, orgs, etc).
- *minDepth* is the minimum depth to show
 - A *minDepth* of 1 means we'll show A in A>B>C. A *minDepth* of 2 means we'll show A>B in A>B>C
- *maxDepth* is how many levels to show.

- If minDepth is 1 and maxDepth is one, then A>B=10 and A>C=5 would get rolled up into A=15 (i.e. we collapse the hierarchy into 1 level).
- If minDepth is 2 and maxDepth is 2, then we'd show A>B and A>C as separate things. If there was A>C>X then the 'x' value would get rolled-up into the 'c' value. etc.

```
SELECT DPQL_COUNT() AS 'Number of Hotdogs'

FROM tickets

WHERE tickets.organization <> NULL AND tickets.custom_data[24] <> NULL

GROUP BY DPQL_HIERARCHY(tickets.custom_data[24], 1, 3) AS 'Type'
```

This example uses a custom field. See how the field has German > Frankfurter > Wurstchen, but on the report we're limiting it to the top-level hotdog type.



New function: DPQL_HIERARCHY_DESCENDS_FROM

- DPQL_HIERARCHY_DESCENDS_FROM can only be used in a WHERE clause
- DPQL_HIERARCHY_DESCENDS_FROM limits what you want to see in a hierarchy. e.g. if you had A>B>C>D and X>Y>Z you might only want to see values under A
- For example, DPQL_HIERARCHY_DESCENDS_FROM(ticket.organization, 5) limits the query to tickets with organizations set to 5 or anything below that.

A query could use this to limit all reports to tickets with the values that descend from the selected value.

```
SELECT DPQL_COUNT() AS 'Open'

FROM tickets WHERE

    tickets.status != 'resolved'

    AND tickets.organization <> NULL

    AND DPQL_HIERARCHY_DESCENDS_FROM(tickets.custom_data[24], ${variable})

GROUP BY tickets.organization.name AS 'Organization'
```

New Function: LAYER WITH

This function allows you to combine multiple result sets in a single query. For example, the results below are generated by the following query.



A simple way to use this stat to show tickets created this month through a DPQL query is:

```
SELECT DPQL_COUNT() as 'stat_value', 'created this month' as 'stat_description'  
  
FROM tickets  
  
WHERE tickets.date_created = %THIS_MONTH%
```

There are a number of data and variations you can select to display:

- `stat_value` — determines the large value shown
- `stat_description` — determines the sub-line
- `unit_left` and `unit_right` are strings that go before/after the value. For example, if you want to show a SUM or AVG value of a currency field, you can set the left unit to £. Or if the number you calculated is a percentage, you could set the right unit to %.
- `default_value` is what to show if `stat_value` returns null. For example, in the above example, if no tickets were created this month, then the count is null, and the report would show "No data". Sometimes it's more useful to just show 0 instead of "No Data". So you could use `... '0'` as `'default_value'` to force 0 as the default value.

Gauge type

The new 'gauge' widget type is useful for displaying information where you want to see the current value of a statistic against a range of possible values for the same statistic at any given time.



In the SELECT clause, you can use the following to create labels and tooltips:

- `tooltip_text` determines the tooltip text. Within the string you can use `[[category]]` as a placeholder for the category (which is the x axis variable) and

[[value]] as the value (which is the value shown on the y axis- usually a count or sum etc).

- `tooltip_text_template` determines the tooltip text based on a template that we evaluate client-side. See below for more on templates.
- `value_axis_title` determines the title shown on . Usually this will be whatever you select the value as, but you can override it here. e.g. `SELECT DPQL_COUNT()` AS 'example' will by default set the title on the y axis to 'example'. Use `value_axis_title` to override this and name it accordingly.
- `value_label_template` sets the template for rendering values along the y axis
- `category_label_template` sets the template for rendering the categories along the x axis.

Templates

Templates are a way of making it easier to render values in different ways vs the "raw" value in DPQL. Essentially, a template is a string that gets rendered through a simple template engine.

Templates apply only to bar and line charts. Here's an example setting the tooltip text using a template:

```
SELECT SUM(ticket_charges.amount) as 'Invoiced Costs', 'Cost' AS 'value_axis_title',
'Invoiced: {{formatCurrency value "GBP"}}' as 'tooltip_text_template'

FROM ticket_charges

WHERE ticket_charges.ticket.organization <> NULL AND ticket_charges.ticket.date_created
= %THIS_YEAR% AND ticket_charges.ticket.status IN ('resolved', 'closed') GROUP BY
ticket_charges.ticket.organization AS 'Organization'
```

In the template string, `{{anything in here}}` is special:

- It can be a bare variable, which include `{{value}}` and `{{category}}`
- Or it can be a function:
 - `formatCurrency` formats the value as a currency value. The first parameter used should be the value to format, and the second is the specific currency to format. For example, if we wanted to show £123.33 we'd use:
 - `{{formatCurrency 123.33 "GBP"}}`
 - `formatNumber` formats a number in ways according to [toLocaleString](#). This would is most likely used in advanced use-cases. The first parameter used should be the value, and the rest can be found in [this document](#). For example
 - `{{formatNumber value maximumFractionDigits=1}}` would

- turn a value like 1 into 1.0 or a value of 223.34874 into 223.3 etc
- `formatPercent` rounds a number to an integer and adds a %
 - `{{formatPercent 5.5}}` — would render as 6% etc.
- `math` carries out simple math. The first param is the value, then comes the operator, then comes the right operator.
 - `{{math 100 "/" 5}}` → 100 would render as 20.

You can also combine functions together with parenthesis. Here's an example combining `formatNumber` with `math`:

```
SELECT AVG(tickets.custom_data[rate_responsiveness])*5 AS 'Responsiveness',
'Responsiveness: {{formatNumber (math value "/" 5) minimumFractionDigits=0
maximumFractionDigits=1}} out of 5' as 'tooltip_text_template'

FROM tickets

WHERE tickets.custom_data[rate_responsiveness].value <> NULL AND
tickets.custom_data[external_lawyer] <> NULL GROUP BY
DPQL_HIERARCHY(tickets.custom_data[external_lawyer], 1) AS 'Firm'
```

If you use a template with `LAYER WITH`, then `{{value}}` and `{{category}}` correspond to the first initial graph. `{{0_value}}` and `{{0_category}}` refers to the second graph; and the number increments for each layer you add. So referring to the first graph would use `value/category`; the next layered one would be `0_value/0_category`, the one after that is `1_value/1_category`, etc

You'd want to define a separate template in each `LAYER WITH` query to set their own tooltip or else they'd all use the same one.

Here's an example of a template with four layers:

<https://gist.github.com/chroder/70bde2256fe3d86fb6ca8141d62319da>

Thanks for reading

If you are using Deskpro Cloud, we will roll out this update to your helpdesk soon.

If you are using Deskpro On-Premise, you can update your helpdesk to the latest version from your Admin Interface.

For more information on product updates associated with this one, take a look at other updates and changes included in the release of [Deskpro 2018.1](#).