

<u>Vidensbase</u> > <u>Developer & Reporting</u> > <u>Creating Reports</u> > <u>Using LIKE and wildcards</u>

Using LIKE and wildcards

Matthew Wray - 2024-08-21 - Kommentarer (0) - Creating Reports

In DPQL you can use the LIKE operator in the WHERE clause to check for certain patterns.

You would use it alongside wildcards:

% represents any number of characters

_ represents one character

Examples

Tickets from a single email domain

An example of this you could use would be if you wanted to look at all tickets from users under a specific email domain.

The query below wouldn't work as the email address is incomplete:

SELECT Tickets.id, tickets.person.emails.email

FROM tickets

WHERE tickets.person.emails.email = 'deskpro.com'

However if rather than = we use Like and the % wildcard we can pull all emails that end in deskpro.com

SELECT Tickets.id, tickets.person.emails.email

FROM tickets

WHERE tickets.person.emails.email LIKE '%deskpro.com'

Tickets from similar email domains

Similarly if we wanted to pull all tickets submitted from $\underline{\text{Deskpro.com}}$ and $\underline{\text{Deskpro.co}}$ uk we could use the following as the second % would bypass the characters specified after deskpro:

SELECT Tickets.id, tickets.person.emails.email

FROM tickets

WHERE tickets.person.emails.email LIKE '%deskpro%'

Wildcard Variations

Different wildcard variations that return support@deskpro.com:

WHERE LIKE Description

LIKE Any values that begin with WHERE person.emails.email 'Support%' support LIKE Any values that end with '%Deskpro.com' deskpro.com $WHERE\ person.emails.email$ LIKE $WHERE\ person.emails.email$ Any values that contain Deskpro '%Deskpro%' Any value that starts with \boldsymbol{S} and $WHERE\ person.emails.email$ LIKE 's%m' ends with M Any value that has a U at the WHERE person.emails.email LIKE '_u%' second position