



How do I manage overriding widget and chat settings

Lauren Cumming - 2023-09-18 - Comment (1) - Deskpro Legacy

All of the settings you find under **Admin > Chat > Site Widget & Chat** can also be overridden on a per-page basis

The default widget looks like this

```
DESKPRO_WIDGET_LOADER::BEGIN--!>
<script type="text/javascript">window.DESKPRO_WIDGET_OPTIONS = {
  "helpdeskUrl": "https://example.deskpro.com/"
};
</script>
<script type="text/javascript" id="dp-widget-loader"
src="https://example.deskpro.com/dyn-assets/pub/build/widget_loader.m
in.js"></script>
<-<! --DESKPRO_WIDGET_LOADER::END
```

You can assign override values to `window.DESKPRO_WIDGET_OPTIONS` to change whatever value you have set in the Admin Interface

```
DESKPRO_WIDGET_LOADER::BEGIN--!>
<script type="text/javascript">window.DESKPRO_WIDGET_OPTIONS = {
  "helpdeskUrl": "https://example.deskpro.com/",
  "language": 1,
  "widget": {
    "type": "bubble",
    "position": "right",
    "enabled": true
  },
  "button": {
    "translations": [
      {
        "language": 1,
        "name": "Help"
      }
    ],
    "size": "medium",
    "colors": {
      "background": "#62ad8c",
      "text": "#fff"
    }
  }
};
```

```
        "text": "#ffffff"
    }
},
"chat": {
    "default_values": {
        "fields": {
            5: "my val",
            6: [7, 8]
        }
    },
    "enabled_custom_fields": [1, 4, 7],
    "request_user_info": true,
    "proactive": true,
    "popup": {
        "translations": [
            {
                "language": 1,
                "title": "Customer Support",
                "message": "Need help? Just reply to start a live chat with one of our team.",
                "heading": "Ask us a question!",
                "subheading": "Our team are online and ready to help with your enquiries. Send us a message to get started."
            }
        ],
        "style": "agent_text_button"
    },
    "begin_mode": "conversation",
    "allow_department_selection": false,
    "waiting_timeout": 150
},
"ticket": {
    "select_department": "custom",
    "default_department": null,
    "select_subject": "custom",
    "default_subject": "",
    "default_values": {
        "subject": "my subject",
        "department": 4,
        "message": "my message",
        "fields": {
            5: "my val",
            6: [7, 8]
        }
    }
}
```

```

        },
        "user_fields": {
            5: "my val",
            6: [7, 8]
        },
        "organization_fields": {
            5: "my val",
            6: [7, 8]
        }
    }
};

</script>
<script type="text/javascript" id="dp-widget-loader" src="https://example.deskpro.com/dyn-assets/pub/build/widget_loader.min.js"></script>
<!-- <!--DESKPRO_WIDGET_LOADER::END

```

root

helpdeskUrl - The URL to the helpdesk

language - The language to force. If you don't set a language, then Deskpro will use the .language the user has from cookies (if any) or guess the users language

widget

.Basic widget options

type - widget view type (column, bubble)

position - widget position location (left, right)

(enabled - is widget enabled (true, false

button

.Widget button options

translations - list of button word translations (language - Deskpro language id, name - button word translation text)

size - button size (small, medium, large)

.(colors - background and text colors for widget button and start chat popup (hex

chat

.Widget live chat options

request_user_info - require user to provide its (name, email, department, custom fields) info before the chat starts

proactive - displays widget chat popup that encourages users to chat with you

popup - chat popup view type (agent_text_button, agents_button, text_button,

`widget_button_agent)`
`(begin_mode - begin chat form view type (conversation, form`

`allow_department_selection - displays department selectbox (true, false) -`
`DEPRECATED`

`select_department` - allows user to select department (custom, default) - using the option `custom` will allow the user to select their own department. The `defaults` option will preselt the department and hide the dropdown.

`default_department` - if `select_department` is `default` then you need to define a default Deskpro department id

`waiting_timeout` - timeout in seconds before ticket form link will be displayed Sorry!
It's taking longer than expected to find an agent to take your chat.
Would you like to submit a ticket instead

`default_values` - Set default values for chat form fields

ticket

.Widget ticket form options

`select_department` - allows user to select department (custom, default) - using the option `custom` will allow the user to select their own department. The `defaults` option will preselt the department and hide the dropdown.

`default_department` - if `select_department` is `default` then you need to define a default Deskpro department id

`select_subject` - (custom - Ask user for a subject, message - `select_subject`, default - Set a subject)

`default_values` - Set default values for ticket form fields